

## BS 5 DG Digital water bath

### Capacity 48 liters - dim. internal tank mm L 620 P 500 H 160

The digital water bath of our production can be used for many applications such as, for example, incubation with precision thermostatic control, precision thermal immersion tests on samples, to subject samples to rapid and uniform heating or more.



#### Construction features

- Construction entirely in AISI 304 stainless steel for maximum corrosion resistance and ease of cleaning.
- Pressed tank with rounded corners to ensure maximum ease of cleaning and hygiene.
- Insulated gap between the tank and the external steel casing (in high quality mineral fiber) to ensure effective thermal insulation, avoid unnecessary waste of electricity and ensure isothermal conditions throughout the tank.
- Semi-circular armored heating elements arranged to cover the entire area of the tank bottom for maximum thermal uniformity, with double perforated cover bottom.
- Temperature detection probe fixed in the inside of the tank to directly take the water temperature value, to ensure the maximum possible accuracy of reading by the digital thermoregulator.
- Complete with tap for complete water drainage.
- Height-adjustable non-slip rubber feet.

#### Standard heat regulation equipment

- PID digital thermoregulator with autotuning with NTC probe
- Temperature range from + 5 ° C above room temperature up to boiling water (lid required in this case)
- Resolution displayed in three digits (0.1 ° C), double display (set point, detected temperature)
- Double overtemperature protection system as standard:
  - a) Adjustable independent safety thermostat (Class 3.1 - DIN 12880), it is activated in case of failure of the main thermoregulator or of the probe or as protection on the water level, with visual alarm (with the relative probe placed inside the tank)
  - b) Safety device with variable intervention threshold according to the set point (at 1.5 ° C fixed over set point, class 2 - DIN 12880), in case of failure of the main thermoregulator, with visual alarm
- Temperature uniformity in the tank:  $\pm 0.25$  ° C at 80 ° C
- Thermostating accuracy (time):  $\pm 0.2$  ° C at 80 ° C
- Compliant with EUROPEAN COUNCIL DIRECTIVES 2006/42 / EC (Machinery Directive), 2014/35 / EU (Low Voltage Directive), 2014/30 / EU (Electromagnetic Compatibility Directive) and with standards EN 6101-1: (2001)
- Factory temperature calibration standard certificate (1 value)

In the image on the side, the bain-marie mod. BS5 is accompanied by:

double sloping lid (see accessories code 8822505)

and electric water mixer (see accessories code 8826001)

MADE IN ITALY

## Technical data

Tank internal dimensions in mm WxDxH	620x500x160
(to the upper edge)	
External dimensions in mm LxWxH	695x575x350
Useful liters capacity	48
Total liter capacity	58
Weight in Kg	19
Absorbed power W	2500

(230V 50-60Hz) except stirring motor cod. 8826001 = 50 Hz

Other voltage / voltage execution on request

Code	Description
<b>9025050</b>	BS 5 DG Digital water bath Capacity 48 liters - dim. internal tank mm L 620 P 500 H 160

## Accessories







Foto	Code	Description
	0101021	
	4400294	
	8822505	
	8826001	

Foto	Code	Description
	8827206	
	8827554	
	8827602	
	8843002	