

Balance mod. PLS720-3A

max load 720 g

- **KERN PLJ 2000-3A** : High-quality milligram scale with ultra-high capacity up to 2100 g - ideal for bulky samples or heavy tare containers.
- Ergonomically optimized keyboard for left and right handed
- **KERN PLJ** : Internal automatic adjustment, to guarantee maximum precision and make operation independent of the place of installation
- Ideal for mobile applications, subject to the approval obligation, for example for the itinerant trade of jewels and gold
- **KERN PLS** : Calibration program CAL, (external calibration weights at extra cost for fine adjustment)
- Glass windshield, standard, for models with weighing plate size \varnothing 110 mm, weighing capacity diam. mm 60 x 150h.
- Rigid protective cover included in the supply.



Backlit LCD display, digit height 17 mm
Weighing pan dimensions (stainless steel)
 \varnothing 110 mm
 \varnothing 160 mm
LxP 200x175 mm

Permissible ambient temperature:
KERN PLS - PLJ from 5 ° C to 35 ° C
KERN PLJ-M from 15 ° C to 30 ° C

Accessories on request:

- Protective hard cover, supply 5 pieces, KERN PLJ-A01S05
- Hook for underfloor weighing, KERN PLJ-A02
- Set for the determination of density of liquids and solids with density $\leq / \geq 1$ for models with

[d] = 0.001 g, KERN ALT-A02 [d] = 0.01 g, KERN PLT-A01

- RS-232 / Ethernet adapter for connection to an IP-based Ethernet network, KERN YKI-01
- For further details, a wide range of accessories and suitable printers, please do not hesitate to contact us.

On demand:

DAKKS certificate (code K3963127)

Code	Description	Max flow rate g	Division g	Linearity g	Min workpiece weight g	Weighing plate diam mm
------	-------------	--------------------	------------	-------------	------------------------------	------------------------------

K3PLS073	Balance mod. PLS720-3A	720	0,001	0,002	0,05	110
----------	---------------------------	-----	-------	-------	------	-----