



Over 50 years in cooperation with the health world, the scientific research, the environmental and quality control world

# PARAFILM® M sealing film 10mm x 38 meters

PARAFILM® M sealing film is used in laboratories to protect samples contained in glass beakers, Erlenmeyer flasks, weighing bottles, graduated cylinders and, because it stretches up to 200%, it also adheres to irregular shapes and surfaces.

Protects the sample from contamination or evaporation and prevents spillage if the container overturns.

PARAFILM® M is free of plasticizers and is essentially made up of polyolefins and paraffin waxes.

If the **PARAFILM®** M comes into contact with food, respect the legal requirements in force on the matter. PARAFILM® M complies with the general requirements of the FDA (Food and Drug Administration) for use below 55 ° C and in compliance with GMP (Good Manufacturing Practice).



PARAFILM® M resists up to 48 hours to many polar substances, eg. saline solutions, inorganic acids and alkaline solutions. After this period of time some embrittlement may arise.

### storage

PARAFILM® M can be stored for at least 3 years without undergoing alterations at a temperature between 7 ° C and 32 ° C and a relative humidity of 50%.

### **Physical properties**

Toxicity: non-toxic

Melting point: 60 ° C

Flash point: 301 ° C

Temperature (continuous use): -45 ° C to +50 ° C

Stretching capacity: 200%

Elongation at tear: 300%

Gas permeability in 24 hours at 23 ° C and 50% relative humidity:

O2 (oxygen):  $\leq$  350 cm3 / m2

N2 (nitrogen): ≤ 105 cm3 / m2

CO2 (carbon dioxide): ≤ 1100 cm3 / m2

Permeability to water vapor in 24 hours at 37 °C and 90% relative humidity: 0.8 g / m2

1/3





Pack of 12 Parafilm L 100 mm x 76 meters
Pack of 6 Parafilm L 500 mm x 15 meters



Over 50 years in cooperation with the health world, the scientific research, the environmental and quality control world

# Effects of exposure for 48 hours at 23 ° C

Acids:

Resistant 36.5% hydrochloric acid
98% sulfuric acid resistant
95% resistant nitric acid *
Alkaline solutions:
Resistant 22% sodium hydrate
Ammonia resistant 28%
Saline solutions:
20% resistant sodium chloride
Potassium permanganate 5% resistant *
lodine solution 0.1 mol / I resistant *
Organic solvents:
Resistant methyl alcohol
Resistant ethyl alcohol
Resistant isopropyl alcohol
Non-resistant diethyl ether
Non-resistant chloroform
Non-resistant carbon tetrachloride
Non-resistant benzene
Non-resistant toluene
* Brown coloring
Further formats available on request:





Over 50 years in cooperation with the health world, the scientific research, the environmental and quality control world

# Accessories on request:

PARAFILM® M cutter, very useful for cleanly storing and cutting the PARAFILM® M sealing film. Suitable for rolls of 50 and 100 mm width.

Code	Description	Width mm	Length m	Pieces per pack.
4400090	PARAFILM® M sealing	100	38	12
	film 10mm x 38 meters			

3/3