Oscillating rotor mod. S4-175 for aluminum frames

Oscillating rotor cod. S4-175 for aluminum frames

Max capacity 4 x 175 ml
Max speed: 4500 rpm
Acceleration: 3600 xg
To be completed with the scales mod. B175 and relative adapters, or with the preformed scales (higher tube capacity) listed below:

	Pre-formed scales with increased tube capacity for S4-175 oscillating rotor		
Code	Description	Total tubes per rotor	Notes for order
B4101532	Aluminum rocker mod. B2-50F for 2 Falcon 50 ml conical bottom tubes (diam.mm 29 x L 116)	8	minimum 4 pieces
B4101582	Aluminum rocker mod. B2-50R for 2 round bottom tubes 50 ml (diam.mm 30 x L 110)	8	minimum 4 pieces
B4101542	Aluminum rocker mod. B7-15F for 7 15 ml Falcon type conical bottom tubes (diam.mm 17 x L120)	28	minimum 4 pieces
B4101592	Aluminum rocker mod. B7-15R for 7 15 ml round bottom test tubes (diam.mm 17 x L 110)	28	minimum 4 pieces
B4101552	Aluminum rocker mod. B12-10 for 12 test tubes type VAC 10 ml (diam.mm 16 x L 1106)	48	minimum 4 pieces
B4101562	Aluminum rocker mod. B14-5 / 7 for 14 test tubes type VAC 5/7 ml (diam.mm 13 x L100)	56	minimum 4 pieces
B4101572	Aluminum rocker mod. B16-5 / 7 for 16 test tubes type VAC 5/7 ml (diam.mm 13 x 75)	64	minimum 4 pieces

Code	**Description**
B4101502	Oscillating rotor mod. S4-175 for aluminum frames

Code	Description

Accessories

Foto	Code	Description
	B4101512	