



Over 50 years in cooperation with the health world, the scientific research, the environmental and quality control world

COMBISTORAGE cabinet 2 compartments with extraction with two doors

with door for ACIDS and BASES and door for FLAMMABLES TYPE 90

COMBISTORAGE FIRE TYPE 90

Construction in electro-galvanized steel sheet with thicknesses of 1; 1.5; 2 mm cold bent with painted removable external structure

with antacid epoxy powders and passage in a thermal tunnel at 200 ° C.

Particular insulation with calcium silicate on panels for high temperature (800 ° C) in high density mineral fiber (free from Fibroceramics)

300 Kg / m3 fixed with ceramic adhesives.

HPL melamine laminate panels with high resistance to even aggressive vapors.

Certification according to EN 14470-1 TYPE 90 and EN 14727.

Leveling by means of adjustable feet with key.

Standard:

- AUTOMATIC CLOSING in case of temperature> 47 ° C.
- LOCK WITH KEY AND DOOR LOCK.
- \bullet Certified automatic closing SYSTEM (70/100 $^{\circ}$ C) of the air inlet and outlet ducts, maintenance free, located on the back of the

wardrobe.

- Suction HOLE diam. 100 mm on the back of the cabinet.
- Non-sparking natural iron HINGES with brass plug.
- 3 cm thermodilating GASKET (DIN 4102).
- "earth" TERMINAL to prevent electrostatic charges.

CHEMICAL COMBISTORAGE

Construction in electro-galvanized steel sheet with thicknesses of 1; 1.5; 2 mm cold bent with removable external structure painted with

antacid epoxy powders and passage in a thermal tunnel at 200 ° C.

Water-repellent melamine laminate panels with high resistance to even aggressive vapors.

Certification according to the new standard EN 14727 and EN 61010.

Level adjustment by means of adjustable feet with key.

Standard:

- LOCK WITH KEY AND DOOR LOCK.
- Suction HOLE diam. 100 mm on the back of the cabinet.
- Non-sparking natural iron HINGES with brass plug.
- "earth" TERMINAL to prevent electrostatic charges.

Available on request:

- additional shelves in painted steel / stainless steel

Possibility of adding plinth for compositions of several modules.

Two-compartment suction cabinet:

- 1 ACIDS / BASES compartment with blind door, equipped with 1 internal shelf in painted steel + 1 in stainless steel
- 1 TYPE 90 FLAMMABLE compartment equipped with tank and grill







Over 50 years in cooperation with the health world, the scientific research, the environmental and quality control world

External dimensions of the product

Height	1985	mm
Width	595	mm
Depth	600	mm
Weight	170	Kg

Code	Description
C4360101	COMBISTORAGE cabinet 2 compartments
	with extraction with two doors