

## Automatic pellet burettes in class AS, Schellbach line, yellow glass, with PTFE tap

Burettes are volumetric calibrated instruments with graduations and taps on the ground. They are used in laboratories for quantitative measurements of smaller liquid volumes in titration.

The burettes are calibrated "Ex" (to be dispensed): the printed volume corresponds to the quantity of liquid dispensed.

A Schellbach strip facilitates accurate reading of the liquid. **Features**

**Class AS** "A" stands for maximum precision, "S" for fast delivery.

The tolerances of class AS are half of the tolerances of class B according to DIN ISO standards.

in borosilicate glass 3.3

according to DIN EN ISO 385

excellent chemical resistance

minimal thermal expansion

high resistance to thermal shocks

with automatic zero adjustment

without intermediate tap

clearly legible numbers and graduations

cone NS 29/32



Pack of 2 pieces

Bottles and rubber bellows can be ordered separately

On request:

- available with certificate of conformity

- with intermediate tap

| Code    | Description  | Capacity ml | Div. | Pieces per pack. |
|---------|--|-------------|------|------------------|
| 1285108 | Automatic pellet burettes in class AS, Schellbach line, yellow glass, with 10 ml PTFE tap            | 10          | 0,05 | 2                |
| 1285115 | Automatic burettes Pellet class AS, Schellbach line, yellow glass, with PTFE stopcock ml 25 div.0.05 | 25          | 0,05 | 2                |
| 1285117 | Automatic pellet burettes in class AS, Schellbach line, yellow                                       | 50          | 0,1  | 2                |

| Code | Description                   | Capacity ml | Div. | Pieces per pack. |
|------|-------------------------------|-------------|------|------------------|
|      | glass, with 50 ml PTFE<br>tap |             |      |                  |