

Thermomixer TS-100

Thermo-Shaker with cooling for microtubes and PCR plates - +25/+100°C

Thermo-Shaker **TS-100C** provides intensive mixing and temperature control of samples in microtest tubes or PCR plate. This model of Thermo-Shaker differs from TS-100 with a possibility of cooling samples down to +4°C.

Features of **TS-100C** meet the highest expectations of users according to many parameters:

1. Fast reaching of specified mixing speed and maintenance of equal amplitude of rotation throughout the Thermo-Shaker block;
2. Stability of maintaining the preset temperature in a wide range throughout the Thermo-Shaker's block surface;
3. LCD display indicates preset and current values of temperature, speed and time of operation;
4. Quiet motor operation, compact size, prolonged service life.

Functions of heating and mixing can be performed both simultaneously and independently.

The instrument is applicable in:

- Genetic analysis — in extraction of DNA, RNA and further sample preparation;
- Biochemical study of enzymatic reactions and processes;
- Extraction of metabolites from cellular material.

Temperature Calibration Function

With the help of the temperature calibration function the user can calibrate the unit approx. $\pm 6\%$ of the selected temperature to compensate differences in the thermal behaviour of tubes from different manufacturers.

There are five heating and cooling blocks available, including a block with a plastic lid for the PCR-plates.

All blocks are mutually interchangeable and can be easily installed on Thermo-Shaker.



| | |
|---|--|
|  | SC-18 - 20 × 0.5 ml + 12 × 1.5 ml microtubes |
|  | SC-18/02 - 20 × 0.2 ml microtubes + 12 × 1.5 ml microtubes |
|  | SC-24N - 24 × 1.5 ml microtubes |
| | SC-24 - 24 × 2 ml microtubes |



SC-96A - 96-well unskirted or semi-skirted microplate (0.2 ml) for PCR or 12 × 8 - 0.2ml strips or 96 tubes of 0.2 ml.

Technical data

| | |
|---|--|
| Temperature setting range | +25°C ... +100°C |
| Temperature control range | +5°C above ambient ... +100°C |
| Temperature setting resolution | 0.1°C |
| Temperature stability | ±0.1°C |
| Temperature accuracy at +37°C | ±0.5°C |
| Average heating speed from +25°C to +100°C | 4°C/min |
| Temperature uniformity over the block at +37°C | ±0.1°C |
| Temperature uniformity over the block at +100°C | ±0.2°C |
| Temperature calibration coefficient range | 0.936...1.063 (± 0.063) |
| Speed control range | 250–1400 rpm |
| Digital time setting | 1 min–96 hrs / non–stop (increment 1 min) |
| Timer sound signal | + |
| Orbit | 2 mm |
| Display | LCD, 16 x 2 signs |
| Microprocessor controlled temperature, mixing speed and operation time | + |
| Maximum continuous operation time | 168 h |
| Overall dimensions (W×D×H) | 220x240x90 mm |
| Weight | 3.7 kg |
| Input current/power consumption | 12 V, 3.5 A / 42 W |
| External power supply | Input AC 100–240 V; 50/60 Hz; Output DC 12 V |

| Code | Description |
|----------|---|
| B7010120 | Thermomixer TS-100 Thermo-Shaker with cooling for microtubes and PCR plates - +25/+100°C |