

SOCOREX micropipette mod. ACURA 835 - ml 2

The Acura manual macropipettes are combining high-tech materials with user-friendly ergonomics. Optimal for in- and outdoor environmental analysis, clinical chemistry and cell culture applications, they offer superior performance and make pipetting safer than ever. Three-year warranty. Smart and reliable volume adjustment

- Single-handed volume setting
- Interchangeable nozzle protection filter
- Justip™ adjustable tip ejector* fitting most tips
- Swift-set user calibration system*
- Shock, UV-light and autoclaving resistance
- Pasteur pipette fitting 2 and 5 mL models



* Socorex patented Also available as fixed volume macropipettes.

Natural ergonomics The challenge for our engineers in combining high tech material with ergonomic design was far above average, and they succeeded excellently. Whether in research or routine applications, the result is an instrument designed and built with the users in mind. The precision pipettes offer much more than superior performance. Enjoy exceptional convenience, comfort, safety and sturdiness, enjoy your Acura®.

Smart and reliable volume setting State-of-the-art micrometric volume setting is performed smoothly and precisely by turning push button. Finely machined click-stops and free rotating cap prevent any unwanted volume alteration.

Display always visible at a glance Located on the front of the instrument, the display window allows set volume to be visible at all times during pipetting. A comforting reassurance for the user.

Adjustable tip ejection Most ergonomically positioned, the large surface, soft padded ejector button provides for low-pressure activation. In addition to ease of tip ejection, the shaft height adjustment system called Justip™ (4 mm span) - controlled by efficient click-stops - allows a wide selection of tips to tightly fit the nozzle.

Swift-Set calibration The swift-set user calibration system - with integrated key and locking mechanism - makes tedious procedures a thing of the past. Easy and precise, it is in full compliance with international standards and recommendations. Seal sicker as safety protection of calibration switch.

Time efficient maintenance Shock, heat, chemicals and UV light resistance is provided by carefully selected materials and good construction. Consequently, maintenance requirements are close to inexistant. Thorough cleaning and sterilisation can be achieved by autoclaving the instrument fully assembled (121°C / 250 °F - 20 minutes).

Environment and sustainability Robustness and longevity of the Socorex® instruments are clear contributions to environmental considerations. Instruments can be disassembled and cleaned, while worn parts replaced. This avoids waste generation as seen on some competitor's models.

Code	Description	Volume	Inaccuracy (E%)	Imprecision (CV%)	Tip Type
21835F02	SOCOREX micropipette mod.	2 ml	< ±0,5%	< 0,2%	2 ml

Code	Description	Volume	Inaccuracy (E%)	Imprecision (CV%)	Tip Type
	ACURA 835 - ml 2				