
KERN **PLS1200-3A**







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	5 mg
Linearity:	3 mg
Minimum weight (USP):	2 g
Readability [d]:	1 mg
Recommended adjusting weight:	1 kg (E2)
Repeatability:	1 mg
Resolution:	1.200.000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	8 h
Weighing capacity [Max]:	1,200 kg
Weighing system:	Force compensation
Weighing units:	tl (Tw) gn ct oz mg ozt tl (HK) g mo dwt lb tl (Singap. Malays)

Display	
Display digit height (large):	1,500 cm
Display digit height (small):	4 mm

Counting	
Counting resolution:	240000
Mininum piece weight at piece counting (Laboratory:	5 mg
Mininum piece weight at piece counting (Normal):	50 mg
Reference weight:	yes



Functions	
Capacity display:	yes
Counting function:	yes
Density determination function:	yes
Percentage determination:	yes
Standby function:	yes
Time display:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	15 °C

Power supply	
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	LIS FURO LIK CH ALIS

Services (ontional)	
Mains adapter/adapter included:	US EURO UK CH AUS
Mains adapter:	Mains adapter external

963-103

DAkkS Certificate:

Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	500 x 360 x 420 mm
Gross weight:	7 kg
Net weight:	4,800 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions draft shield (ÃxH):	160 70
Dimensions housing (WxDxH):	210 x 340 x 120 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	210 x 340 x 160 mm
Revolving screw feet:	yes
Weighing space (ÃxH):	150 60
Weighing surface (d):	110

KERN **PLS1200-3A**



High-quality precision scale with comfortable graphic display and enormous weighing range

Piktogramme

STANDARD



OPTION



FACTORY

