





RED

LINE





The RED-Line is a self-confident statement in microscope hardware. Motic, as an experienced manufacturer of microscopes, has listened carefully to the special demands of the educational market. Unexperienced users will need reliable and easy-to-use instruments with repeatable image results to take their first steps into the "world of small things". Taking these special requirements into consideration, this catalogue presents a complete new line of biological and stereo microscopes. New illumination technologies and further clever ideas with focus on young users have been implemented to make microscopic teaching more simple and effective.





REVOLUTIONARY

EDUCATIONAL




Once again Motic with its RED-Line strides ahead of the competition by offering quality instruments for a limited budget. Our 10-Year Limited Warranty is supported by a complete parts inventory that assures availability even beyond the warranty period. A Motic microscope is therefore a solid investment that will pay off with years of hassle-free and effective work.

REDLINE CATALOGUE CONTENTS

INTRODUCTION	02
RED100 SERIES	04
RED200 SERIES	10
RED30 SERIES	16
MOTICAM SERIES RED50X	22












RED100 SERIES

THE RED100 SERIES REPRESENTS THE IDEAL MICROSCOPE LINE FOR PRIMARY, SECONDARY AND HIGH SCHOOL STUDENTS









Student dedication of the RED100 Series starts with the microscope head. Depending on budget and teaching situation, monocular, dual-view or binocular options are available. For easy storage in a cabinet, the eyepiece tubes may be rotated 180°. The fixation by a countersunk screw prevents inadmissible removal by students.

The well positioned focus controls can easily be found by following the curves of the microscope stand. A relaxed seating position allows an intuitive evaluation of the sample by the coaxial coarse/fine focus mechanism. The convenient carrying handle on the back of the stand simplifies storage or just transport.

The optics of a microscope of course is the most important component for an instructive teaching. Motic supplies his RED100 Series with high quality EA objectives; Achromats with good colour reproduction, contrast and a time saving field flatness: flat samples like sections or smears can be evaluated fast and efficiently. The reversed positioning of the nosepiece gives good space for placing or exchanging the glass slides, avoiding the risk of damaging the sample or the objectives.

The standard WF10X/18mm eyepieces work perfectly fine with the EA Achromats. In binocular packages, diopter adjustment is possible on the left eyepiece tube. An eyepiece pointer is integral part of any RED100 package, allowing the teacher to point out regions of interest to the student. In order to prevent un-authorised removal, again countersunk screws fix the eyepieces and help to keep the equipment complete.


All RED100 microscopes incorporate a cordless LED illumination. Especially in educational environments, LEDs display several advantages over the traditional halogen bulbs: extended life time (>10.000 hours), no heat development (improved user safety), low power consumption (one single charge provides 70 hours of use) and a modern sensation of colour without corrective blue filter.

RED100 SERIES

- Gliding stage with "One touch" sample clips or Mechanical stage with sample holder
- > High quality EA objectives
- > LED illumination



	S		The second secon
RED	100	RED101	RED 120
NOSEPIECE			
Triple	٠	•	
Quadruple			٠
STAGE			
Gliding	٠	٠	
Mechanical			٠
FOCUSING SYSTEM			
Coarse & fine	٠	٠	•
Coaxial			




ENRICO Bruno srl - TORINO - www.enrico-bruno.it RED100 SERIES | 07

SPECIFICATIONS	RED 100	RED 101	RED 120	RED 130	RED 131	RED 132
Optical System						
Finite optical system, 160mm	•	•	٠	٠	•	•
Observation Tube						
Monocular	•		٠	٠		
Dual view monocular		٠			•	
Binocular Siedentopf type						•
Inclination						
45° inclined, 360° rotating	•		٠	٠		
30° inclined and vertical, 360° rotating		٠			•	
30° inclined, 360° rotating						٠
Interpupillary distance						
55-75mm						•
Diopter adjustment						
On the left tube , +/- 5 diopter						•
Eyepieces						
WF10X/18mm with pointer, lockable	•	•	•	•	•	•
Nosepiece						
Reversed triple revolving nosepiece with click stops	•	•				
Reversed quadruple revolving nosepiece with click stops			•	•	•	•
EA Achromatic Objectives (DIN)						
4X/0.10, 10X/0.25, 40X/0.65/S	•	•				
4X/0.10, 10X/0.25, 40X/0.65/S, 100X/1.25/S-Oil			•	•	•	٠
Stage						
Gliding stage with "one-touch" sample clips	•	•				
Built-in low position coaxial mechanical stage with sample holder			-		-	
and 77 x 25mm X/Y travel range			•	•	•	•
Stage size						
110mm x 110mm	•	•				
120mm x 120mm			•	•	•	•
Condenser						
Built-in 0.65 N.A. condenser with iris diaphragm	•	•				
Spiral mounted 1.25 N.A. Abbe condenser with iris diaphragm			•	•	•	•
Focus mechanism						
Separated coarse and fine focusing system with tension adjustment	t •	•	٠			
Coaxial coarse and fine focusing system with tension adjustment				•	•	•
Fine focus precision						
2µm minimum increment	٠	•	٠	٠	٠	•
Z-axis movement						
7mm			•	•	٠	•
13mm	•	•				
Illumination						
Battery/Cordless LED 20mA, 3.5V, 70mW with intensity control	•	•	٠	٠	•	•

ENRICO Bruno srl - TORINO - www.enrico-bruno.it

THE ACCESSORIES

RED100 SERIES



Huygens eyepiece H5X/14.5mm Widefield eyepiece WF10X/18mm Widefield eyepiece WF15X/12mm Widefield eyepiece WF20X/11mm

MICROMETER EYEPIECES

Micrometer eyepiece WF10X/18mm,100 divisions in 10mm and crosshair

RETICLES

0

0/091

AB

38 ·O

Reticle with 100 divisions in 10mm and crosshair (Ø19mm) Reticle holder for 18mm eyepiece

ACHROMATIC OBJECTIVES - EA

Achromatic objective EA 4X/0.10 Achromatic objective EA 10X/0.25 Achromatic objective EA 20X/0.40 Achromatic objective EA 40X/0.65/S Achromatic objective EA 60X/0.85/S Achromatic objective EA 100X/1.25/S - 0il

ACHROMATIC OBJECTIVES, LOCKABLE

Achromatic objective 4X/0.10 Achromatic objective 10X/0.25 Achromatic objective 40X/0.65/S Achromatic objective 100X/1.25/S - Oil

SPARE PARTS

Dust cover (size B) Aluminium box Immersion oil 5ml Cleaning kit Lens tissue paper Motic slides 76x25mm Motic coverslips 22x22mm

SPARE BULBS LED 20mA, 3.5V, 70mW

E A 40

RED200 SERIES

THE RED200 SERIES IS DESIGNED FOR ADVANCED BIOLOGY STUDENTS, TEACHERS AND LAB TECHNICIANS






The RED200 Series features the comfortable Siedentopf head concept with an interpupillary distance from 55-75mm. To compensate sight defects, the left eyetube allows a diopter adjustment of +/- 5 dpt.

The advanced level of the RED200 Series is also underlined by the large and heavy microscope body which ensures better stability, especially when adapting a camera. The large coaxial focusing controls are easily accessible; the fine focus drive has a minimum increment of 2µm for smooth and precise focusing "through" the sample. The cord-hanger at the back of the microscope helps in case of transport or storage, just wind up the cable.

The RED200 Series also displays an improved level of optical performance. Motic's Semi-Plan (SP) objectives deliver a supreme contrast with crisp and clear images over a large field of view (20mm). All microscopes come with a set of 4X, 10X, 40X and 100X/Oil objectives to cover the regular magnification range. No need to say that 40X and 100X-Oil objectives come with an integrated spring mechanism, preventing damage to the front lens and specimen in case of unexperienced users.


To transform your microscope into a presentation station for teaching purposes, a trinocular microscope version is recommended. The RED223 and RED233 packages already include an 0.5X c-mount for the simple adaption of a digital camera.



RED200 SERIES

- > High precision Coaxial focusing controls
- > New Semi-Plan objectives
- > Koehler illumination
- > Intensity control adjustment







SPECIFICATIONS	RED 211	RED220	RED223	RED 230	RED2
Optical System					
Finite optical system, 160mm	•	•	•	•	•
Observation Tube					
Monocular	•				
Binocular Siedentopf type		•		•	
Trinocular Siedentopf type (0,5X c-mount adapter included)			•		•
Inclination					
30° inclined, 360° rotating	•	•	•	•	•
Interpupillary distance					
55-75mm		•	•	•	•
Diopter adjustment					
On the left tube , +/- 5 diopter		•	٠	•	•
Eyepieces					
WF10X/20mm	•	•	•	•	•
Nosepiece					
Reversed quadruple revolving nosepiece with click stops	•	•	•	•	٠
Achromatic Semi-Plan objectives - SP					
4X/0.10, 10X/0.25, 40X/0.65/S, 100X/1.25/S-0il	•	•	٠	•	٠
Stage					
Built-in low position coaxial mechanical stage with sample holder					
and 77 x 50mm X/Y travel range	•	•	•	•	•
Stage size					
140mm x 135mm	•	•	٠	•	•
Condenser					
Spiral mounted 1.25 N.A. Abbe condenser with iris diaphragm	•	•	•		
Focusable and centerable 1.25 N.A. Abbe condenser with iris diaphragm				•	•
Focus mechanism					
Coaxial coarse and fine focusing system with tension adjustment	•	•	•	•	•
Fine focus precision					
2µm minimum increment	•	•	•	•	•
Z-axis movement					
13mm	•	•	•		
19mm				•	•
Illumination				-	5
LED 3W with intensity control	•	•	•		
LED 3W Koehler illumination with intensity control		-	-	•	•

THE ACCESSORIES





Huygens eyepiece H5X/14.5mm Widefield eyepiece WF10X/20mm Widefield eyepiece WF15X/12mm Widefield eyepiece WF20X/11mm

MICROMETER EYEPIECES

Micrometer eyepiece WF10X/20mm,100 divisions in 10mm and crosshair

RETICLES

Reticle with 100 divisions in 10mm and crosshair (Ø21mm) Reticle holder for 20mm eyepiece

ACHROMATIC SEMI-PLAN OBJECTIVES - SP

Achromatic Semi-Plan objective SP 4X/0.10 (WD=17mm) Achromatic Semi-Plan objective SP 10X/0.25 (WD=6.4mm) Achromatic Semi-Plan objective SP 20X/0.40 (WD=0.73mm) Achromatic Semi-Plan objective SP 40X/0.65/S (WD=0.45mm) Achromatic Semi-Plan objective SP 60X/0.85/S (WD=0.1mm) Achromatic Semi-Plan objective SP 100X/1.25/S-0il (WD=0.14mm)

PLAN ACHROMATIC OBJECTIVES - PL

Plan achromatic objective PL 4X/0.10 (WD=17mm) Plan achromatic objective PL 10X/0.25 (WD=1.5mm) Plan achromatic objective PL 20X/0.40 (WD=0.55mm) Plan achromatic objective PL 40X/0.65/S (WD=0.4mm) Plan achromatic objective PL 60X/0.85/S (WD=0.1mm) Plan achromatic objective PL 100X/1.25/S - 0il (WD=0.15mm)

POLARIZING SET Polarizing set B.209NT

Rotating table

PHOTO AND C-MOUNT CAMERA ADAPTERS

0.35X C-mount camera adapter for 1/3" chip sensors
0.5X C-mount camera adapter for 1/3" and 1/2" chip sensors
0.65X C-mount camera adapter for 2/3" chip sensors
1X C-mount camera adapter (no lens)
Photo adapter (requires one of the photo eyepieces below)
2.5X photo eyepiece (to be used with Photo adapter)
4X photo eyepiece (to be used with Photo adapter)

SPARE PARTS

11.0/031

blan 4/01


Eyecups (pair) Dust cover (size C) Immersion oil 5ml Aluminium box Cord hanger (pair) Cleaning kit Lens tissue paper Motic slides 76x25mm Motic coverslips 22x22mm

SPARE BULBS LED light assembly 3W

ENRICO Bruno srl - TORINO - www.enrico-bruno.it RED200 SERI

RED30 SERIES

A STEREO MICROSCOPE SERIES OF SUPERB PERFORMANCE; IDEAL FOR FIRST STEPS INTO THE WORLD OF MICROSCOPY







Stereo microscopes have got the best preconditions for an easy access to microscopy. No need for sample preparation, just take a flower from the school garden or an insect from the window bench. Low magnifications allow the student to understand the next smaller dimension step, an upright image helps in orientation.

Motic's RED30S implements a 2-step magnification changer for both sample overview and detail information. A more convenient approach is presented by the 1:3 zoom optics of the RED39Z. Both stereos come with incident and transmitted LED illumination for bright, white and even illumination. All advantages of LED illumination can be found here: bright light, long lifetime, no heat development for the safety of user and living samples.

The transmitted light is implemented in a large microscope base with a minimum height: an easy and convenient manipulation of the sample is possible as the hands may rest on the table top. The microscope base is completely sealed to protect the illuminator from liquids that might be spilled. Fresh water samples can easily be evaluated without any risk. In case of checking a glass slide, Motic's "one-touch" sample clips help to fix the specimen.

The incident light is dedicated to non-transparent samples like minerals, fossils or plants. As incident and transmitted light can be regulated independently, illumination can be optimized for each specific sample. The cordless concept of the LED illumination with rechargeable batteries is ideal for field work activities; the large carrying handle as well as the light construction of the instrument suits even younger students.

Motics RED-Line stereo microscopes have combined reliable mechanics, superb optics and a user-friendly LED illumination. A fine combination that will deliver impressive image results for an enjoyable start into science.

RED30 SERIES

- > User-friendly design
- > Integrated LED illumination
- > Carrying handle for easy transportation







SPECIFICATIONS	RED30S	RED3
Optical System		
Greenough	•	•
Observation Tube		
Binocular head	•	•
Inclination		
45° inclined	•	
45° inclined, 180° rotating		•
Interpupillary distance		
52-69mm	•	
51-77mm		•
Diopter adjustment		
On left tube , +/- 5 diopter	•	
On both tubes , +/- 5 diopter		•
Objectives system		
Turret changer with LED incident illumination	•	
Zoom, ratio 3:1		•
Objectives magnification		
2X - 4X	•	
1X ~ 3X		•
Working distance		
50mm	•	
60mm		•
Stand		
Fixed arm type stand	•	•
Base		
225 x 179mm	•	•
Column/Arm		
200mm high	•	
202mm high		•
Head holder		
Fixed	•	
For Ø66mm stereo head with LED incident illumination		•
Focus mechanism		
Coarse focusing system with tension adjustment	•	•
Focusing stroke		
46mm		•
47mm	•	
Incident illumination	_	
Battery/Cordless LED 3.5V / 100mW with intensity control	•	•
Transmitted illumination		9
Battery/Cordless LED 3.5V / 100mW with intensity control	•	•

ENRICO Bruno srl - TORINO - www.enrico-bruno.it

THE ACCESSORIES

W30X/8

RED30 SERIES

EYEPIECES (PER PIECE)

Widefield eyepiece WF5X/22mm Widefield eyepiece WF10X/20mm Widefield eyepiece WF15X/13mm Widefield eyepiece WF20X/10mm Widefield eyepiece WF30X/8mm

MICROMETER EYEPIECES

Micrometer eyepiece WF10X/20mm,140 divisions in 14mm and crosshair Micrometer eyepiece WF10X/20mm, 70 divisions in 14mm Micrometer eyepiece WF10X/20mm, 360° protractor with 1° divisions and crosshair Micrometer eyepiece WF10X/20mm, 100 divisions in 10mm

RETICLES

Reticle with 140 divisions in 14mm and crosshair (Ø23mm) Reticle with 70 divisions in 14mm (Ø23mm) Reticle with 360° protractor with 1° divisions and crosshair (Ø23mm) Reticle with 100 divisions in 10mm (Ø23mm)

SPARE PARTS

White stage plate, Ø 50mm Black stage plate, Ø 50mm Frosted stage plate, Ø 50mm Dust cover (size B) Eyecups (pair) Cord hanger (pair) Aluminium box Cleaning kit Lens tissue paper

SPARE BULBS

LED Assembly top light for RED30S LED Assembly top light for RED39Z LED Assembly bottom light

MOTICAM SERIES

EXCELLENT LIVE IMAGES FOR TEACHING AND CLASSROOM WORK



TABLET SOLUTIONS

MONITOR YOUR PROGRESS WITH THESE TOUCH SCREEN TABLET CAMERAS AND CONVERT YOUR MICROSCOPE INTO A STANDALONE DIGITAL MICROSCOPE SYSTEM; WITHOUT THE NEED OF A COMPUTER



Tablet Solutions will help microscope users visualize, edit and share the microscope images, enabling computer-free digital microscopy.

The Moticam Tablet Cameras consist of a customized Android tablet connected to a microscopy imaging camera. The android tablet is easily detachable and replaceable and is completely separate from the camera, providing maximum flexibility.

In just one click you will be able to capture high-quality images, measure and edit them as well as record HD videos. All it takes is a touch of your finger!







The individual situation in a classroom may be unique. To share positive image results nevertheless is a common teaching task. The combination of a RED-Line microscope with a member of the Moticam Series enables to display and to share excellent live images for presentations and discussions. The camera package also includes the easy-to-use Motic Images Plus software which allows to save still images and to record videos, as well as many other edition options. Living samples thus can be evaluated in an appropriate way.

For a group work approach in classrooms, we have two options with Wi-Fi data transfer that may suit perfectly. The Moticam X, which allows the access of multiple tablets or computers, so one microscope as imaging source is sufficient to feed up to 6 student devices with images for homework; or the Moticam X2 which is the advanced version. The difference is that the Moticam X2 has its own battery, and it allows you to integrate it to your own network either via Wi-Fi or via Ethernet cable, allowing more users to be connected. Capture, edit and share your images with our free App MotiConnect.

Adapting a Moticam to your microscope is quite easy: the eyepiece adapters allow to use even a monocular model as an image source. Trinocular RED-Line microscopes already come with the necessary c-mount adapter for the photo port.

Discover the possibilities and benefits of connecting a Moticam camera onto your RED-Line microscope. Multiply your teaching options, improve teaching efficiency!



Our Moticam selection suitable for you

Looking for more? Ask for our complete Moticam range of cameras



RED50X ·)) WI-FI DIGITAL MICROSCOPE

BASIC MICROSCOPE WITH INTEGRATED WI-FI CAMERA OF 1.3MP, WILL MAKE YOUR LESSONS INTERACTIVE AND ENJOYABLE



Optical System Observation Tube Inclination Camera sensor Output Eyepieces Nosepiece **Objective classification** Objectives Objective mounting thread Stage Stage size Condenser Focus mechanism Z-axis movement Illumination Power supply

1	Finite optical system, 160mm
è	Monocular with built in digital X type Wi-Fi camera
ı	30° inclined, 360° rotating
r	CMOS 1/3" - 1.3MP - 1280 x 1024 pixels
t	Wi-Fi transmission up to 1.3MP
5	WF10X/18mm
è	Reversed triple revolving nosepiece with click stops
1	Achromatic objectives, DIN
5	4X/0.10, 10X/0.25, 40X/0.65/S - Lockable
ł	W 4/5"x1/36" (RMS standard)
è	Gliding stage with "one-touch" sample holder
e	Ø105mm
r	Built in 0.65 N.A. with disc diaphragm
1	Coarse focusing system
t	8mm
ı	LED 20mA, 3.5V, 70mW with intensity control
/	Charger 100V/240V (CE) and rechargeable batteries





