

MINI INCUBATOR

INCUBATORS

MAIN FEATURES:

- > Small Benchtop Incubator
- > Door with large window
- > Precise temperature control by hydraulic thermostat
- > Ideal for microbiology or hematology applications
- > Corrosion resistant chamber

TECHNICAL SPECIFICATIONS	
Model	Mini Incubator
Voltage	230V, 50/60Hz 120V, 50/60Hz
Power	70W
Temperature range	Ambient + 5°C to 60°C
Controls	Analog
Stability	±0,6°C at 37°C
Accuracy	±5°C
Capacity	10 liters
Ambient operation range	4°C to 40°C
Net weight	8,3kg
Chamber dimensions (WxDxH)	230 x 220 x 200mm
Dimensions (WxDxH)	285 x 280 x 335mm

ORDERING INFORMATION	Cod.
INCUBATOR 10 Analog	
230V / 50 - 60 Hz	D5780400



Analog 10I incubator is compact and economically priced, yet offers features not typically found in a basic incubator. The housing is all metal, as is the door frame. See-through acrylic door lets you view contents without opening the door. One shelf is included, and can be adjusted to two different levels - additional shelves can be purchased to increase storage capacity.

The heating elements in incubator are incorporated into the bottom and sides of the aluminum chamber. This provides better temperature stability and uniformity than other incubators in it's class.

A grommet hole in the top of the unit can hold a thermometer for accurate temperature setting.