KFRN 440-51N

The classic balance in the laboratory





Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	3 g
Linearity:	2 g
Readability [d]:	1 g
Recommended adjusting weight:	2 kg (M2); 2 kg (M2)
Repeatability:	1 g
Resolution:	4000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	10 min
Weighing capacity [Max]:	4 kg
Weighing system:	Strain gauge
Weighing units:	tl (HK) tol g mo kg lb dwt tl (Tw) oz ozt

Display	
Display digit height (large):	1,500 cm
Counting	
Counting resolution:	2000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

Display

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	

Environmental conditions

80 % Maximum humidity: 35 °C Maximum operating temperature: $5\,^{\circ}C$ Minimum ambient temperature:

Power supply

9 V Block Battery: Charging time: 10 h 100-240V AC 50/60Hz 0.5A Input voltage:

Mains adapter/adapter included: UK EURO CH US 20 h Operating time:

Operating time (Backlight off): 20 h

Rechargeable battery: Rchrg. battery optional

Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category

Brand: **KERN** Category: Balances

Product Group: Precision balance

Packaging & shipping

Delivery: 24 h Dimensions packaging (WxDxH): 347 x 207 x 170 mm Gross weight: 1,644 kg Net weight: 1,121 kg

Parcel service

Construction

Shipping method:

Casing material: **Plastic** Dimensions housing (WxDxH): 165 x 230 x 80 mm Dimensions of weighing plate 153 x 172 x 80 mm (WxDxH): Material weighing plate: stainless steel Weighing surface (WxD): 150 x 170 mm

Piktogramme

STANDARD



OPTION



KERN 440-51N

The classic balance in the laboratory



