

Precision Balances KERN EW-N · EG-N



STANDARD



B



C



1



2

Accessories

- Protective working cover, scope of delivery: 5 items, for models with weighing plate size
A, B KERN EG-A05S05
C KERN EG-A09S05
- Internal rechargeable battery pack, operating time up to 12 h with backlight, charging time approx. 12 h, for models with weighing plate size
A, B KERN EG-A04
C KERN EG-A06
- 2** Large glass draught shield with 3 sliding doors for easy access to the items being weighed. Weighing space W×D×H 150×140×130 mm, KERN EG-A03
- Loop for underfloor weighing, for models with weighing plate size
A, B KERN EG-A07
C KERN EG-A08
- Minimum weight of sample, smallest weight to be weighed, depending on the required process accuracy, only in combination with a DAkkS calibration certificate, KERN 969-103
- Equipment qualification: compliant qualification concept which includes the following validation services, Installation Qualification (IQ), Operating Qualification (OQ), for details see page 230
- Further details, plenty of further accessories and suitable printers see *Accessories*

The classic balance with robust tuning fork measuring system

Features

- 1** KERN EG: Internal adjustment in the case of a change in temperature and time-controlled at defined intervals, guarantees high degree of accuracy and makes the balance independent of its location of use
- Stable temperature behaviour
- Short stabilisation time
- Shock proof construction
- High corner load performance
- Capacity display: A bargraph display lights up to show how much of the weighing range is still available
- Totalising of pieces when counting
- Draught shield standard for models with weighing plate size **A**, weighing space W×D×H 158×130×78 mm

- Protective working cover included with delivery

Technical data

- Large LCD display, digit height 17 mm
- Dimensions weighing surface, stainless steel
A Ø 118 mm, see larger picture
B W×D 170×140 mm **C** W×D 180×160 mm
- Overall dimensions W×D×H
A 185×235×165 mm **B, C** 180×235×75 mm
- Net weight
A ca. 2,0 kg, **B** ca. 1,6 kg, **C** ca. 4,0 kg
- Permissible ambient temperature 10 °C/30 °C

STANDARD



OPTION



























FACTORY



Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Linearity	Weighing plate	Net weight	Verification	Options
	g	g	g	g	g		kg	M O KERN	DAkkS Calibr. Certificate
KERN									DAkkS KERN
EW 220-3NM	220	0,001	-	-	± 0,002	A	1,4	-	963-127
EW 420-3NM	420	0,001	-	-	± 0,003	A	1,4	-	963-127
EW 620-3NM	620	0,001	-	-	± 0,003	A	1,4	-	963-103
EW 820-2NM	820	0,01	-	-	± 0,01	B	1,6	-	963-127
EW 2200-2NM	2200	0,01	-	-	± 0,01	C	3,0	-	963-127
EW 4200-2NM	4200	0,01	-	-	± 0,02	C	3,0	-	963-127
EW 6200-2NM	6200	0,01	-	-	± 0,03	C	3,0	-	963-104
EW 12000-1NM	12000	0,1	-	-	± 0,2	C	3,0	-	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

EG 220-3NM	220	0,001	0,01	0,02	± 0,002	A	2,0	965-216 U	963-127
EG 420-3NM	420	0,001	0,01	0,02	± 0,003	A	1,8	965-216 U	963-127
EG 620-3NM	620	0,001	0,01	0,1	± 0,004	A	2,0	965-201 U	963-103
EG 2200-2NM	2200	0,01	0,1	0,5	± 0,01	C	4,0	965-216 U	963-127
EG 4200-2NM	4200	0,01	0,1	0,5	± 0,02	C	4,0	965-216 U	963-127

 Internal adjusting Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 Interface for second balance For direct connection of a second balance	 Hold function (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Conformity Assessment The time required for conformity assessment is specified in the pictogram
 Adjusting program CAL For quick setting up of the balance's accuracy. External adjusting weight required	 Network interface For connecting the scale to an Ethernet network	 Protection against dust and water splashes IPxx The type of protection is shown in the pictogram	 DAkkS calibration possible (DKD) The time required for DAkkS calibration is shown in days in the pictogram
 EasyTouch Suitable for the connection, data transmission and control through PC or tablet	 KERN Communication Protocol (KCP) It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	 Suspended weighing Load support with hook on the underside of the balance	 Factory calibration (ISO) The time required for Factory calibration is shown in days in the pictogram
 Memory Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 GLP/ISO log intern The balance displays weight, date and time, independent of a printer connection	 Battery operation Ready for battery operation. The battery type is specified for each device	 Package shipment The time required for internal shipping preparations is shown in days in the pictogram
 Alibi memory Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 GLP/ISO log Printer With weight, date and time. Only with KERN printers.	 Rechargeable battery pack Rechargeable set	 Pallet shipment The time required for internal shipping preparations is shown in days in the pictogram
 KERN Universal Port (KUP) allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort	 GLP/ISO log Printer With weight, date and time. Only with KERN printers.	 Universal plug-in power supply with universal input and optional input socket adapters for A) EU, CH, GB B) EU, CH, GB, US C) EU, CH, GB, US, AUS	
 RS-232 Data interface To connect the balance to a printer, PC or network	 Piece counting Reference quantities selectable. Display can be switched from piece to weight	 Plug-in power supply 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available	
 RS-485 Data interface To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 Recipe level A The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 Integrated power supply unit Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request	
 USB Data interface To connect the balance to a printer, PC or other peripherals	 Recipe level B Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 Weighing principle Strain gauges Electrical resistor on an elastic deforming body	
 Bluetooth* Data interface To transfer data from the balance to a printer, PC or other peripherals	 Totalising level A The weights of similar items can be added together and the total can be printed out	 Weighing principle Tuning fork A resonating body is electromagnetically excited, causing it to oscillate	
 WIFI Data interface To transfer data from the balance to a printer, PC or other peripherals	 Percentage determination Determining the deviation in % from the target value (100 %)	 Weighing principle Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings	
 Control outputs (optocoupler, digital I/O) To connect relays, signal lamps, valves, etc.	 Weighing units Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details	 Weighing principle Single cell technology Advanced version of the force compensation principle with the highest level of precision	
 Analogue interface to connect a suitable peripheral device for analogue processing of the measurements	 Weighing with tolerance range (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model		